

# TMS-Lite

Voice Mail and Auto Attendant System



Two and four port, Voice Mail/Auto Attendant System with 10 hours respectively. Both configurations contain 128 Mailboxes.

## The affordable and feature rich solution for business and the growing Small Office Home Office (SOHO)

TMS-Lite offers incredible capability for small and medium sized business as well as residences with a family member working from home. Calls are transferred promptly to intended destinations without interrupting others. Greetings of your choice can be offered for each incoming line. Up to 128 mailboxes assure messages are promptly taken for the appropriate party. A variety of notification options assure that messages are delivered, even to your cell phone if you like! TMS-Lite is the solution for your business or residence incorporating the latest technology at an affordable price.

## Leading edge technology

TMS-Lite incorporates leading edge technology including flash memory and digital signal processing (DSP). It is small and compact, weighing just about a pound and can be mounted unobtrusively, requiring little space. TMS-Lite is an energy asset to your operation using no more electricity than a 60 watt light bulb.

## Complete array of voice messaging features

TMS-Lite supports a full array of voice messaging and auto attendant features, multiple concurrent language capabilities, off-site notification and fax tone detection (CNG). The system is programmed via a user-friendly Windows-based Voice Mail Utility Program (VUP) or touch-tone phone. With its Voice Mail, Auto Attendant and System Administration features, TMS-Lite offers the advantages of a PC-based system, but at a lower cost.

TMS-Lite can be integrated with most types of telephone systems through analog ports by using In-Band DTMF protocol.



FCC part 15 class B

## TMS-Lite Configurations

---

- 2 Ports / 10 Hours
- 4 Ports / 10 Hours
- Field upgradable from 2 ports to 4 ports

## Voice Mail Features

---

- 128 Real/Virtual Mailboxes
- Announcer Mailbox
- Five Mailbox Groups (5 messaging groups)
- Customized Greetings, Mailboxes and Language per Mailbox
- Message Retrieve, Save, Copy, Delete, Forwarding
- Date and Time Stamp (Software optional – on or off)
- Skip Forward to next Message
- Automatic Message Purge (Configurable by system administrator)
- Password Protection
- Do Not Disturb Mode
- Message Delivery: Pager, Work Extension, Mobile, Home
- Message Notification: Message Waiting LCD/LED, Interrupted Dial Tone (dependent on host switch)
- Call Recording (dependent on host switch)
- **23 Available Languages:** Any three are available on the TMS-Lite at one time; American English, Arabic, British English, Chinese, Czech, Danish, Dutch, Finnish, Flemish, French, German, Greek, Hebrew, Indonesian, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Thai, Turkish.

## Automated Attendant Features

---

- Multilingual Option
- Opening Greetings for Different Operating Modes: Day, Night, Holiday, Break (Lunch)
- Automatic Mode/System Schedules
- Call Transfer: Supervised, Semi-Supervised, Non-Supervised
- 39 Script Menus (each with up to 9 minutes recording time) with single digit access
- Default transfer to operator
- Supervised, semi-supervised and release transfer modes, per extension
- Directory Listing (dial by name, first or last, configurable)
- Fax Detection and Routing (CNG detect and transfer)
- Direct Dialing to extensions
- Greeting by Port
- Answering on first ring
- Audio-text

## System and Administration Features

---

- Reports: Configurations, Memory Usages, Traffic Reports
- Programming: PC programming (Windows based Utility Program), Touch-Tone Phone (using DTMF tones)
- Security Passwords: System Administrator, Operator, Mailbox Owner
- Integration with most existing PBX and Key Systems: In-Band DTMF Integration, Out-Band Serial Port RS-232 (SMDI) Integration
- Automatic Gain Control (AGC)
- Adjustable Recording Length (1-9 Minutes per Mailbox/Script)
- Disconnect Detection: Silence Detection, Loop Current, Busy Tone, Continuous Dial Tone, Disconnect Tone, DTMF Code Detection

## Specifications

---

- Dimensions (H x W x D): 7.9" x 8.7" x 1.6"
- Weight: 1.1 lbs.
- External Power Supply: 120 VAC / 9 VDC



TransTel Communications, Inc.  
1095 Jupiter Park Drive, Suite 7  
Jupiter, Florida 33458  
561 747-4466 Phone  
561 747-4578 Fax  
800 872-6785 North America Toll Free  
E-Mail: sales@transtelcommunications.com